

SAMSUNG

ELECTRONICS

Approval



TO :

DATE : Oct. 8. 2009

SAMSUNG TFT-LCD**MODEL NO. : LTN156AT05-H01**

NOTE : Extension code [-H01]
 → LTN156AT05-**H01**
 Surface type [**Glare**]

Any Modification of Spec is not allowed without SEC' permission.

APPROVED BY :

PREPARED BY :

Mia So**Application Engineer part 1, Device Solution (LCD)****SAMSUNG ELECTRONICS CO., LTD.**
Samsung Secret

CONTENTS

Revision History	----- (3)
General Description	----- (4)
1. Absolute Maximum Ratings	----- (5)
1.1 Absolute Ratings of environment	
1.2 Electrical Absolute Ratings	
2. Optical Characteristics	----- (7)
3. Electrical Characteristics	----- (10)
3.1 TFT LCD Module	
3.2 Backlight Unit	
3.3 LED Driver	
4. Block Diagram	----- (13)
4.1 TFT LCD Module	
5. Input Terminal Pin Assignment	----- (14)
5.1 Input terminal pin assignment	
5.2 LVDS Interface	
5.3 Timing Diagrams of LVDS For Transmitting	
5.4 Input Signals, Basic Display Colors and Gray Scale of Each Color.	
5.5 Pixel format	
6. Interface Timing	----- (19)
6.1 Timing Parameters	
6.2 Timing Diagrams of interface Signal	
6.3 Power ON/OFF Sequence	
7. Outline Dimension	----- (21)
8. Packing	----- (23)
9. Markings & Others	----- (24)
10. General Precautions	----- (26)
11. EDID	----- (28)

Samsung Secret

GENERAL DESCRIPTION**DESCRIPTION**

LTN156AT05 is a color active matrix TFT (Thin Film Transistor) liquid crystal display (LCD) that uses amorphous silicon TFT as switching devices. This model is composed of a TFT LCD panel, a driver circuit and a backlight unit. The resolution of a 15.6" contains 1366 x 768 pixels and can display up to 262,144 colors. 6 O'clock direction is the optimum viewing angle.

FEATURES

- High contrast ratio
- HD (1366 x 768 pixels) resolution
- High Color Gamut (Typical 60%)
- Low power consumption
- Fast response time
- LED Back Light with embedded LED Driver
- DE (Data enable) only mode
- 3.3V LVDS Interface
- Onboard EEDID chip
- Green product (RoHS compliance)

APPLICATIONS

- Notebook PC
- If the usage of this product is not for PC application, but for others, please contact SEC

GENERAL INFORMATION

Item	Specification	Unit	Note
Display area	344.232(H) x 193.536(V) (15.6" HD diagonal)	mm	
Driver element	a-Si TFT active matrix		
Display colors	262,144		
Number of pixel	1366 x 768	pixel	16:9
Pixel arrangement	RGB vertical stripe		
Pixel pitch	0.252(H) x 0.252(V) (TYP.)	mm	
Display Mode	Normally white		
Surface treatment	Haze 0, Hard-Coating 3H		

Samsung Secret

Mechanical Information

Item		Min.	Typ.	Max.	Unit	Note
Module size	Horizontal (H)	358.8	359.3	359.8	mm	
	Vertical (V)	209.0	209.5	210.0	mm	
	Depth (D)	-	-	5.5	mm	(1)
Weight		-	430	450	g	

Note (1) Measurement condition of outline dimension

. Equipment : Bernier Calipers

. Push Force : 500g · f (minimum)

1. ABSOLUTE MAXIMUM RATINGS


1.1 ENVIRONMENTAL ABSOLUTE RATINGS

Item	Symbol	Min.	Max.	Unit	Note
Storage temperate	TSTG	-20	60	°C	(1)
Operating temperate (Temperature of glass surface)	TOPR	0	50	°C	(1)
Shock (non-operating)	Snop	-	240	G	(2),(4)
Vibration (non-operating)	Vnop	-	2.41	G	(3),(4)

Note (1) Temperature and relative humidity range are shown in the figure below.

95 % RH Max. ($40^{\circ}\text{C} \geq T_a$)

Maximum wet - bulb temperature at 39°C or less. ($T_a > 40^{\circ}\text{C}$) No condensation



(2) 2ms, half sine wave, one time for $\pm X$, $\pm Y$, $\pm Z$.

(3) 5 - 500 Hz, random vibration, 30min for X, Y, Z.

(4) At testing Vibration and Shock, the fixture in holding the Module to be tested have to be hard and rigid enough so that the Module would not be twisted or bent by the fixture.

Samsung Secret

1.2 ELECTRICAL ABSOLUTE RATINGS

(1) TFT LCD MODULE

 $V_{DD} = 3.3V$, $V_{SS} = GND = 0V$

Item	Symbol	Min.	Max.	Unit	Note
Power Supply Voltage	V_{DD}	$V_{DD} - 0.3$	$V_{DD} + 0.3$	V	(1)
Logic Input Voltage	V_{IN}	$V_{DD} - 0.3$	$V_{DD} + 0.3$	V	(1)

Note (1) Within T_a (25 ± 2 °C)

Samsung Secret

2. OPTICAL CHARACTERISTICS


The following items are measured under stable conditions. The optical characteristics should be measured in a dark room or equivalent state with the methods shown in Note (5).
Measuring equipment : TOPCON SR-3

* Ta = 25 ± 2 °C, V_{DD}=3.3V, fv= 60Hz, f_{DCLK} = 69.3MHz, IF = 20 mA

Item		Symbol	Condition	Min.	Typ.	Max	Unit	Note
Contrast Ratio (5 Points)		CR	Normal Viewing Angle $\phi = 0$ $\theta = 0$	500	-	-	-	(1), (2), (5)
Response Time at Ta (Rising + Falling)		T _{RT}		-	16	25	msec	(1), (3)
Average Luminance of White (5 Points)		Y _{L,AVE}		170	200	-	cd/m ²	IF=20mA (1), (4)
Color Chromaticity (CIE)	Red	R _x		0.585	0.615	0.645	-	(1), (5) SR-3
		R _y		0.325	0.355	0.385		
	Green	G _x		0.305	0.335	0.365		
		G _y		0.580	0.610	0.640		
	Blue	B _x		0.120	0.150	0.180		
		B _y		0.070	0.100	0.130		
	White	W _x		0.283	0.313	0.343		
		W _y	0.299	0.329	0.359			
Viewing Angle	Hor.	θ_L	CR ≥ 10 At center	30	45	-	Degrees	(1), (5) SR-3
		θ_H		30	45	-		
	Ver.	ϕ_H		10	15	-		
		ϕ_L		20	35	-		
13 Points White Variation		δ_L		-	1.4	1.6	-	(6)

Samsung Secret

Note 1) Definition of Viewing Angle : Viewing angle range($10 \leq C/R$)




Note 2) Definition of Contrast Ratio (CR) : Ratio of gray max (Gmax), gray min (Gmin) at 5 points(4, 5, 7, 9, 10)

$$CR = \frac{CR(4) + CR(5) + CR(7) + CR(9) + CR(10)}{5}$$

Points : (4), (5), (7), (9), (10) at the figure of Note (6).


Note 3) Definition of Response time :



Note 4) Definition of Average Luminance of White : measure the luminance of white at 5 points.

Average Luminance of White ($Y_{L,AVE}$)

$$Y_{L,AVE} = \frac{Y_{L4} + Y_{L5} + Y_{L7} + Y_{L9} + Y_{L10}}{5}$$




Samsung Secret

Note 5) After stabilizing and leaving the panel alone at a given temperature for 30 min , the measurement should be executed. Measurement should be executed in a stable, windless, and dark room. 30 min after lighting the backlight. This should be measured in the center of screen.


IF current : 20.0mA

Environment condition : $T_a = 25 \pm 2 \text{ }^{\circ}\text{C}$



Note 6) Definition of 13 points white variation (δL), CR variation(C_{VER}) [① ~ ⑬]

$$\delta L = \frac{\text{Maximum luminance of 13 points}}{\text{Minimum luminance of 13 points}}$$



Samsung Secret

3. ELECTRICAL CHARACTERISTICS

3.1 TFT LCD MODULE

Ta= 25 ± 2°C

Item		Symbol	Min.	Typ.	Max.	Unit	Note
Voltage of Power Supply		V _{DD}	3.0	3.3	3.6	V	
Differential Input Voltage for LVDS Receiver Threshold	High	V _{IH}	-	-	+100	mV	V _{CM} = +1.2V
	Low	V _{IL}	-100	-	-	mV	
Vsync Frequency		f _v	-	60	-	Hz	
Hsync Frequency		f _H	-	46.8	-	KHz	
Main Frequency		f _{DCLK}	67.2	69.3	70.6	MHz	
Rush Current		I _{RUSH}	-	-	1.5	A	(4)
Current of Power Supply	White	I _{DD}	-	330	-	mA	(2),(3)*a
	Mosaic		-	470	-	mA	(2),(3)*b
	V. stripe		-	500	600	mA	(2),(3)*c

Note (1) Display data pins and timing signal pins should be connected. (GND = 0V)

(2) f_v = 60Hz, f_{DCLK} = 69.3MHz, V_{DD} = 3.3V , DC Current.

(3) Power dissipation pattern


*a) White Pattern



*b) Mosaic Pattern


Display Brightest Gray Level →

Display Darkest Gray Level →




Samsung Secret


*c) 1dot Vertical stripe pattern



4) Rush current measurement condition



V_{DD} rising time is 470us



Samsung Secret

3.2 BACK-LIGHT UNIT

Ta= 25 ± 2 °C

Item	Symbol	Min.	Typ.	Max.	Unit	Note
LED Forward Current	IF	19	20	21	mA	
LED Forward Voltage	VF	-	3.2	-	V	
LED Array Voltage	VP	-	35.2	37.4	V	VF x 11 LEDs
Power Consumption	P	-	-	4.0	W	w/ Driver
Operating Life Time	Hr	12,000	-	-	Hour	(1)

Note (1) Life time (Hr) of LEDs can be defined as the time in which it continues to operate under the condition Ta= 25 ± 2 °C and IF = 20.0 mA until one of the following event occurs.

1. When the brightness becomes 50% or lower than the original.

3.3 LED Driver

Ta= 25 ± 2 °C


Item	Symbol	Min.	Typ.	Max.	Unit	Note
Input Voltage	V _{in}	6	12	20	V	
Enable Control Level	V	0	-	5	V	ON Level : 2V~5V OFF Level : 0V ~ 0.5V
PWM Control Level	V _{PWM}	0	-	5	V	High Level : 2.7V~5V Low Level : 0V ~ 0.3V
PWM Control Duty Ratio	%	10	-	100	%	
PWM Input Frequency	BLIM	0.2	-	1	KHz	

Note - Test Equipment : Fluke 45


Samsung Secret

4. BLOCK DIAGRAM

4.1 TFT LCD Module



4.2 LED connection and placement



Samsung Secret

5. INPUT TERMINAL PIN ASSIGNMENT


5.1. Input terminal pin assignment (LVDS, Connector : 20455-040E-0 by I-PEX or equivalent)

No.	Signal	Description
1	NC	No Connection
2~3	AVDD	Power Supply, 3.3V (typical)
4	DVDD	DDC 3.3V power
5	NC	No Connection
6	SCL	DDC Clock
7	SDA	DDC Data
8	Rin0-	-LVDS differential data input (R0-R5, G0)
9	Rin0+	+LVDS differential data input (R0-R5, G0)
10	GND	Ground
11	Rin1-	-LVDS differential data input (G1-G5, B0-B1)
12	Rin1+	+LVDS differential data input (G1-G5, B0-B1)
13	GND	Ground
14	Rin2-	-LVDS differential data input (B2-B5, HS, VS, DE)
15	Rin2+	+LVDS differential data input (B2-B5, HS, VS, DE)
16	GND	Ground
17	ClkIN-	-LVDS differential clock input
18	ClkIN+	+LVDS differential clock input
19	GND	Ground
20~21	NC	No Connection
22	GND	Ground
23~24	NC	No Connection
25	GND	Ground
26~27	NC	No Connection
28	GND	Ground
29~30	NC	No Connection
31~33	VBL-	LED Ground
34	NC	No Connection
35	BLIM	PWM for luminance control (200~1KHz, 3.3V, 10~100%)
36	BL_Enable	BL On/Off (On:2.0~3.3V, Off: 0~0.5V)
37	NC	No Connection
38~40	VBL+	LED Power Supply 6V~20V

Samsung Secret

5.2 LVDS Interface : Transmitter SN75LVDS86 or Compatible

Pin No.	Name	RGB Signal	Pin No.	Name	RGB Signal
44	TxIN0	R0	12	TxIN11	G5
45	TxIN1	R1	13	TxIN12	B0
47	TxIN2	R2	15	TxIN13	B1
48	TxIN3	R3	16	TxIN14	B2
1	TxIN4	R4	18	TxIN15	B3
3	TxIN5	R5	19	TxIN16	B4
4	TxIN6	G0	20	TxIN17	B5
6	TxIN7	G1	22	TxIN18	Hsync
7	TxIN8	G2	23	TxIN19	Vsync
9	TxIN9	G3	25	TxIN20	DE
10	TxIN10	G4	26	TxCLKIN	Clock


LVDS INTERFACE

Note 1): The LCD Module uses a 100ohm resistor between positive and negative lines of each receiver input.

Samsung Secret

5.3 Timing Diagrams of LVDS For Transmission

LVDS Receiver : Integrated T-CON



Samsung Secret

5.4 Input Signals, Basic Display Colors and Gray Scale of Each Color

Color	Display	Data Signal																	Gray Scale Level	
		Red						Green						Blue						
		R0	R1	R2	R3	R4	R5	G0	G1	G2	G3	G4	G5	B0	B1	B2	B3	45		B5
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	-
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0	-
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	-
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	-
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1	-
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	-
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
Gray Scale Of Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R0
	Dark	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1
	↑	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R2
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	R3~R60
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		
	↓	1	0	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	R61
	Light	0	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	R62
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	R63
Gray Scale Of Green	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G0
	Dark	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	G1
	↑	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	G2
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	G3~G60
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		
	↓	0	0	0	0	0	0	1	0	1	1	1	1	0	0	0	0	0	0	G61
	Light	0	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	G62
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0	G63
Gray Scale Of Blue	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	B0
	Dark	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	B1
	↑	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	B2
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	B3~B60
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:		
	↓	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	B61
	Light	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	B62
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	B63

Note 1) Definition of gray :


Rn: Red gray, Gn: Green gray, Bn: Blue gray (n=gray level)

Note 2) Input signal: 0 =Low level voltage, 1=High level voltage

Samsung Secret

Approval

5.5 Pixel Format in the display




Samsung Secret

6. INTERFACE TIMING

6.1 Timing Parameters

Signal	Item	Symbol	Min.	Typ.	Max.	Unit	Note
Frame Frequency	Cycle	TV	774	780	810	Lines	
Vertical Active Display Term	Display Period	TVD	-	768	-	Lines	
One Line Scanning Time	Cycle	TH	1430	1480	1530	Clocks	
Horizontal Active Display Term	Display Period	THD	-	1366	-	Clocks	

6.2 Timing diagrams of interface signal




Samsung Secret

6.3 Power ON/OFF Sequence

Approval

: To prevent a latch-up or DC operation of the LCD module, the power on/off sequence should be as the diagram below.



Timing (ms)	Remarks
$0.5 < T_1 \leq 10$	V _{DD} rising time from 10% to 90%
$0 < T_2 \leq 50$	Delay from V _{DD} to valid data at power ON
$0 < T_3 \leq 50$	Delay from valid data OFF to V _{DD} OFF at power Off
$500 \leq T_4$	V _{DD} OFF time for Windows restart
$200 \leq T_5$	Delay from valid data to B/L enable at power ON
$200 \leq T_6$	Delay from valid data off to B/L disable at power Off
$0 < T_7 \leq 10$	V _{DD} falling time from 90% to 10%
$10 < T_8$	Delay from valid data on to LED driver V _{in} rising time 10%
$10 < T_9$	Delay from LED driver V _{in} falling time 10% to valid data Off
$0.5 < T_{10} \leq 10$	LED V _{in} rising time from 10% to 90%
$0.5 < T_{11} \leq 10$	LED V _{in} falling time from 90% to 10%
$10 < T_{12}$	Delay from LED driver V _{in} rising time 90% to PWM ON
$10 < T_{13}$	Delay from PWM Off to LED driver V _{in} falling time 10%
$10 < T_{14}$	Delay from PWM ON to B/L Enable ON
$10 < T_{15}$	Delay from B/L Enable Off to PWM Off

Note : Backlight may flash if interface signal remains floating state at invalid period.

Samsung Secret




7. Mechanical Outline Dimension

Approval

Refer to the next page


Samsung Secret

Doc.No.	LTN156AT05-H01	Rev.No	04-A00-G-091009	Page	21 / 30
----------------	----------------	---------------	-----------------	-------------	---------



<USER HOLE SCREW HOLE DEPTH>

BM SHIFT SPEC.






- IA-BI < 1.0 (mm)
- IC-DI < 1.0 (mm)
- IBM1 ≥ 1.0 (mm)

- * NOTE
1. SIGNAL INTERFACE CONNECTOR TO BE SPECIFIED AS BELOW.
- MAKER : I-PEX OR COMPATIBLE
- INPUT CONNECTOR : I-PEX 20455-#40#-## OR EQUIVALENT
 2. LED CONNECTOR FOR BACKLIGHT TO BE SPECIFIED AS BELOW.
- MAKER : UJU Electronics
- PART NO : 51441-1041
 3. CALIFERS MEASURING FORCE : 750 ± 250 gf/cm
 4. MAXIMUM SCREW TORQUE : MAX 2.5 Kgf-cm(5TIMES)
 5. WEIGHT : 520 g MAX
 6. IN ORDER TO AVOID IC DAMAGE, IT IS NOT ALLOW THAT OVERLAPPING OF CABLES OR ANTENNAS, CAMERA, WLAN, WWAN, OVER THESE COF LOCATIONS.

REV. DATE	DESCRIPTION OF REVISION	REASON	CHK'D BY
001	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
002	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
003	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
004	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
005	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
006	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
007	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
008	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
009	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
010	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
011	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
012	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
013	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
014	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
015	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
016	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
017	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
018	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
019	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
020	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
021	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
022	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
023	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
024	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
025	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
026	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
027	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
028	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
029	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
030	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
031	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
032	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
033	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
034	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
035	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
036	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
037	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
038	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
039	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
040	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
041	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
042	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
043	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
044	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
045	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
046	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
047	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
048	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
049	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
050	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
051	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
052	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
053	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
054	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
055	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
056	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
057	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
058	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
059	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
060	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
061	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
062	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
063	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
064	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
065	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
066	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
067	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
068	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
069	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
070	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
071	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
072	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
073	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
074	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
075	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
076	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
077	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
078	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
079	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
080	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
081	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
082	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
083	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
084	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
085	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
086	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
087	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
088	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
089	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
090	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
091	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
092	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
093	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
094	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
095	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
096	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
097	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
098	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
099	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001
100	1-PEX 20455-#40#-##	1-PEX 20455-#40#-##	LTN156AT05-001

8. PACKING**1. CARTON(Internal Package)****(1) Packing Form**

Corrugated Cardboard box and Corrugated form as shock absorber

(2) Packing Method**CUSHION BOTTOM****PANEL : 2EA/SLIT****CUSHION TOP, BOTTOM***Note* (1) Total : Approx. 12400g

(2) Acceptance number of piling : 20 sets

(3) Carton size : 344(W) X 432(D) X 329(H)

Samsung Secret

(3)Packing Material

No	Part name	Quantity
1	Static electric protective sack	20
2	Packing case (Inner box) included shock absorber	1 set
3	Pictorial marking	2 pcs
4	Carton	1 set


9. MARKINGS & OTHERS

A nameplate bearing followed by is affixed to a shipped product at the specified location on each product.


(1)Parts number : LTN156AT05

(2)Revision code : 3 letters

(3)Lot number : X X X X XXX XX X H01



(4) Nameplate Indication




Parts name : LTN156AT05
 Lot number : XXXXXXXXXX
 Inspected work week : 0910 (2009 year 10rd week)
 Product Revision Code : H01


Samsung Secret

Approval

(5) High voltage caution notice



(6) Packing small box attach



Samsung Secret

10. GENERAL PRECAUTIONS

Approval

1. Handling

- (a) When the module is assembled, It should be attached to the system firmly using every mounting holes. Be careful not to twist and bend the modules.
- (b) Refrain from strong mechanical shock and / or any force to the module. In addition to damage, this may cause improper operation or damage to the module and CCFT back-light.
- (c) Note that polarizers are very fragile and could be easily damaged. Do not press or scratch the surface harder than a HB pencil lead.
- (d) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, Staining and discoloration may occur.
- (e) If the surface of the polarizer is dirty, clean it using some absorbent cotton or soft cloth.
- (f) The desirable cleaners are water, IPA (Isoprophyl Alcohol) or Hexane.
Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
- (g) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, legs or clothes, it must be washed away thoroughly with soap.
- (h) Protect the module from static, it may cause damage to the C-MOS Gate Array IC.
- (i) Use fingerstalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (j) Do not disassemble the module.
- (k) Do not pull or fold the lamp wire.
- (l) Do not adjust the variable resistor which is located on the back side.
- (m) Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.
- (n) Pins of I/F connector shall not be touched directly with bare hands.

Samsung Secret

Doc.No.	LTN156AT05-H01	Rev.No	04-A00-G-091009	Page	26 / 30
---------	----------------	--------	-----------------	------	---------

2. STORAGE

- (a) Do not leave the module in high temperature, and high humidity for a long time.
It is highly recommended to store the module with temperature from 0 to 35 °C and relative humidity of less than 70%.
- (b) Do not store the TFT-LCD module in direct sunlight.
- (c) The module shall be stored in a dark place. It is prohibited to apply sunlight or fluorescent light during the store.

3. OPERATION

- (a) Do not connect, disconnect the module in the "Power On" condition.
- (b) Power supply should always be turned on/off by following item 6.3
"Power on/off sequence".
- (c) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- (d) The standard limited warranty is only applicable when the module is used for general notebook applications. If used for purposes other than as specified, SEC is not to be held reliable for the defective operations. It is strongly recommended to contact SEC to find out fitness for a particular purpose.

4. OTHERS

- (a) Ultra-violet ray filter is necessary for outdoor operation.
- (b) Avoid condensation of water. It may result in improper operation or disconnection of electrode.
- (c) Do not exceed the absolute maximum rating value. (the supply voltage variation, input voltage variation, variation in part contents and environmental temperature, so on)
Otherwise the module may be damaged.
- (d) If the module displays the same pattern continuously for a long period of time, it can be the situation when the image "sticks" to the screen.
- (e) This module has its circuitry PCB's on the rear side and should be handled carefully in order not to be stressed.

Samsung Secret

Doc.No.	LTN156AT05-H01	Rev.No	04-A00-G-091009	Page	27 / 30
----------------	----------------	---------------	-----------------	-------------	---------

11. EDID

Approval

Address (HEX)	FUNCTION	Value	BIN	DEC	ASCII or Data	Notes
		HEX				
00	Header	00	00000000	0		EDID Header
01		FF	11111111	255		
02		FF	11111111	255		
03		FF	11111111	255		
04		FF	11111111	255		
05		FF	11111111	255		
06		FF	11111111	255		
07		00	00000000	0		
08	ID Manufacturer Name	4C	01001100	76	S	3 character ID
09		A3	10100011	163	E C	"SEC"
0A	ID Product Code	51	01010001	81	[Q]	
0B		36	00110110	54	[6]	
0C	32-bit serial no.	00	00000000	0		
0D		00	00000000	0		
0E		00	00000000	0		
0F		00	00000000	0		
10	Week of manufacture	00	00000000	0		
11	Year of manufacture	12	00010010	18	2008	2008
12	EDID Structure Ver.	01	00000001	1	1	EDID Ver. 1.0
13	EDID revision #	03	00000011	3	3	EDID Rev. 3
14	Video input definition	80	10000000	128		
15	Max H image size	22	00100010	34	34	34 cm(approx)
16	Max V image size	13	00010011	19	19	19 cm(approx)
17	Display Gamma	78	01111000	120	2.2	Gamma 2.2
18	Feature support	0A	00001010	10		
19	Red/green low bits	87	10000111	135		10000111
1A	Blue/white low bits	F5	11110101	245		11111110
1B	Red x/ high bits	94	10010100	148	0.580	Red x0.580= 1001010010
1C	Red y	57	01010111	87	0.340	Red y0.340= 0101011100
1D	Green x	4F	01001111	79	0.310	Green x0.310= 0100111101
1E	Green y	8C	10001100	140	0.550	Green y0.550= 1000110011
1F	Blue x	27	00100111	39	0.155	Blue x0.155= 0010011111
20	Blue y	27	00100111	39	0.155	Blue y0.155= 0010011111
21	White x	50	01010000	80	0.313	White x0.313= 0101000001
22	White y	54	01010100	84	0.329	White y0.329= 0101010001
23	Established timing 1	00	00000000	0		
24	Established timing 2	00	00000000	0		
25	Established timing 3	00	00000000	0		

Samsung Secret

26	Standard timing #1	01	00000001	1		not used
27		01	00000001	1		
28	Standard timing #2	01	00000001	1		not used
29		01	00000001	1		
2A	Standard timing #3	01	00000001	1		not used
2B		01	00000001	1		
2C	Standard timing #4	01	00000001	1		not used
2D		01	00000001	1		
2E	Standard timing #5	01	00000001	1		not used
2F		01	00000001	1		
30	Standard timing #6	01	00000001	1		not used
31		01	00000001	1		
32	Standard timing #7	01	00000001	1		not used
33		01	00000001	1		
34	Standard timing #8	01	00000001	1		not used
35		01	00000001	1		
36	Detailed timing/monitor descriptor #1	12	00010010	18	69.3	Main clock= 69.3 MHz
37		1B	00011011	27		
38		56	01010110	86	1366	Hor active=1366 pixels
39		72	01110010	114	114	Hor blanking=114 pixels
3A		50	01010000	80		4bit : 4bit
3B		00	00000000	0	768	Vertical active=768 lines
3C		0C	00001100	12	12	Vertical blanking=12 lines
3D		30	00110000	48		4bit : 4bit
3E		30	00110000	48	48	H sync. Offset=48 pixels
3F		20	00100000	32	32	H sync. Width=32 pixels
40		25	00100101	37	2 5	V sync. Offset=2 lines V sync. Width=5 lines
41		00	00000000	0		2bit : 2bit :2bit :2bit
42		58	01011000	88	344	H image size= 344 mm(approx)
43		C2	11000010	194	194	V image size = 194 mm(approx)
44		10	00010000	16		
45		00	00000000	0		No Horizontal Border
46		00	00000000	0		No Vertical Border
47		19	00011001	25		
48	Detailed timing/monitor descriptor #2	00	00000000	0		Manufacturer Specified (Timing)
49		00	00000000	0		
4A		00	00000000	0		
4B		0F	00001111	15		
4C		00	00000000	0		
4D		00	00000000	0		Value=HSPWmin / 2
4E		00	00000000	0		Value=HSPWmax / 2
4F		00	00000000	0		Value=Thbpmin / 2
50		00	00000000	0		Value=Thbpmax / 2
51		00	00000000	0		Value=VSPWmin / 2
52		00	00000000	0		Value=VSPWmax / 2
53		00	00000000	0		Value=Tvpmin / 2
54		00	00000000	0		Value=Tvpmax / 2
55		1E	00011110	30		Thpmin=value*2 + HA pixelclks
56		B4	10110100	180		Thpmax=value*2 + HA pixelclks
57		02	00000010	2		Tvpmin=value*2 + VA lines
58		74	01110100	116		Tvpmax=value*2 + VA lines
59		00	00000000	0		Module revision

Samsung Secret

Approval

5A	Detailed timing/monitor descriptor #3	00	00000000	0		ASCII Data String Tag
5B		00	00000000	0		
5C		00	00000000	0		
5D		FE	11111110	254		
5E		00	00000000	0		
5F		53	01010011	83	[S]	
60		41	01000001	65	[A]	
61		4D	01001101	77	[M]	
62		53	01010011	83	[S]	
63		55	01010101	85	[U]	
64		4E	01001110	78	[N]	
65		47	01000111	71	[G]	
66		0A	00001010	10	[^]	
67		20	00100000	32	[]	
68		20	00100000	32	[]	
69		20	00100000	32	[]	
6A		20	00100000	32	[]	
6B		20	00100000	32	[]	
6C	Detailed timing/monitor descriptor #4	00	00000000	0		Monitor Name Tag (ASCII)
6D		00	00000000	0		
6E		00	00000000	0		
6F		FE	11111110	254		
70		00	00000000	0		
71		31	00110001	49	[I]	
72		35	00110101	53	[5]	
73		36	00110110	54	[6]	
74		41	01000001	65	[A]	
75		54	01010100	84	[T]	
76		30	00110000	48	[0]	
77		35	00110101	53	[5]	
78		2D	00101101	45	[=]	
79		48	01001000	72	[H]	
7A		30	00110000	48	[0]	
7B		31	00110001	49	[I]	
7C		0A	00001010	10	[^]	
7D		20	00100000	32	[]	
7E	Extension Flag	00	00000000	0		
7F	Checksum	15	00010101	21		

Samsung Secret